

## SBKQC 'QuickClick' Intermediate Jaw - 32kN



### Characteristics

- GO-NOGO colour coding for reliable adaptation to the pressing chain

### suitable for

- Can be used only in connection with pressing chains QC and SSK (not included in scope of supply)
- Stainless steel, steel: max. NS 54 mm
- Copper, copper alloys: max. NS 54 mm
- Multi-layer pipe / PEX pipe: max. NS 110 mm / 4"
- The stated information is system-dependent.

### Technical data

Force	32 kN
-------	-------

Compatibility	UAP332, UAP432, UAP4, UAP3, UAP2/UNP2, HPU2, PKUAP2
---------------	---

## SBKUAP4 Intermediate Jaw - 32kN



### Characteristics

- GO-NOGO colour coding for reliable adaptation to the pressing chain

### suitable for


- Can be used only in connection with BP pressing chain LP (not included in scope of supply)
- Stainless steel, steel: max. NS 108 mm / 4"
- Copper, copper alloys: max. NS 108 mm / 4"
- Multi-layer pipe / PEX pipe: max. NS 110 mm / 4"
- The stated information is system-dependent.













### Technical data

Force	32 kN
-------	-------

Compatibility	UAP432, UAP4, PKUAP4
---------------	----------------------

## Jaw/Machine Compatibility



		MAP215	MAP219	UAP332	UAP432
	SBM	•			
	UWM	• in connection with WE			
	SBMX		•		
	UWMX		•		
	SB			•	•
	UW			•	•
	WE	•	•	•	•
	SBKQC			•	•
	SB- KUAP4				•
	QC			• in connection with SBKQC	• in connection with SBKQC
	SSK			• in connection with SBKQC	• in connection with SBKQC
	BP ... LP				• in connection with SBKUAP4