


# Klauke

## MAP219 19kN Battery Powered Hydraulic Pressing Machine



### Technical data

Linear force	19 kN
Weight	1.8 kg
Dimensions	395 x 80 x 118 mm
Ambient temperature	-10 °C up to 40 °C
Battery	18 V, Li-Ion
Battery charger	230 V (110 V on request)
Number of pressings	Approx. 150 (NS 20 / 1.5 Ah battery)
Pressing jaw holder	rotates 350°
Bluetooth	•
Realtime clock	•
OLED display	•
Hydraulic Pressure Control	•


### suitable for













#### SBMX pressing jaw Mini Extra 19 kN



- Stainless steel, steel: max. NS 35 mm / 1-1/4"
- Copper, copper alloys: max. NS 35 mm / 1-1/4"
- Multilayer pipe / PEX pipe: max. NS 40 mm / 1-1/2"
- The stated information is system-dependent.

## Jaw/Machine Compatibility



		MAP215	MAP219	UAP332	UAP432
	SBM	•			
	UWM	• in connection with WE			
	SBMX		•		
	UWMX		•		
	SB			•	•
	UW			•	•
	WE	•	•	•	•
	SBKQC			•	•
	SB- KUAP4				•
	QC			• in connection with SBKQC	• in connection with SBKQC
	SSK			• in connection with SBKQC	• in connection with SBKQC
	BP ... LP				• in connection with SBKUAP4