

QC 'QuickClick' Pressing Sling - 32kN



Characteristics

- Reliable pressing with clamping function on the fitting before and after the pressing process

suitable for

- Can be used only in connection with adapter jaw SBKQC (not included in scope of supply)
- Stainless steel, steel: max. NS 54 mm / 108 mm / 4"
- Copper, copper alloys: NS 54 mm / 108 mm / 4"
- Multi-layer pipe / PEX pipe: max. NS 110 / 4"
- The stated information is system-dependent.

Technical data

Force	32 kN
Compatibility	UAP332, UAP432, UAP4, UAP3, UAP2/UNP2, HPU2, PKUAP2

BP Pressing Sling (Low Pressure) - 32kN



Characteristics

- 4-segment pressing technology for optimum pressing
- Building installation
- Reliable pressing with clamping function on the fitting before and after the pressing process
- Sturdy chain lock absorbs high clamping forces


suitable for













- Can be used only in connection with adapter jaw SBKUAP4 (not included in scope of supply)
- Stainless steel, steel: max. NS 108 mm / 4"
- Copper, copper alloys: NS 108 mm / 4"
- Multi-layer pipe / PEX pipe: max. NS 110 / 4"
- The stated information is system-dependent.

Technical data

Force	32 kN
Compatibility	UAP432, UAP4L, UAP4, PKUAP4

Jaw/Machine Compatibility



		MAP215	MAP219	UAP332	UAP432
	SBM	•			
	UWM	• in connection with WE			
	SBMX		•		
	UWMX		•		
	SB			•	•
	UW			•	•
	WE	•	•	•	•
	SBKQC			•	•
	SB- KUAP4				•
	QC			• in connection with SBKQC	• in connection with SBKQC
	SSK			• in connection with SBKQC	• in connection with SBKQC
	BP ... LP				• in connection with SBKUAP4