





Art427

EPDM PN6 Flanged Flexible Connector



Features

- Flanged PN6 BS4504
- Zinc plated carbon steel flanges
- Nylon cord fabric with steel reinforcement




Technical data

Max pressure: 6 Bar


Working temp: -20°C to +100°C

N.	Part Name	Materials
1	Body	EPDM
2	Reinforcement	Nylon Cord Wire
3	Pressure Ring	Steel Wire
4	Flange	Carbon Steel


DN	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"	5"	6"	8"	10"	12"
D	120	130	140	160	190	210	240	265	320	375	440
D1	90	100	110	130	150	170	200	225	180	335	395
b	14	14	14	14	16	16	18	18	20	22	22
L	130	130	130	130	130	130	130	130	130	130	130
Ø-n	14-4	14-4	14-4	14-4	18-4	18-4	18-8	18-8	18-8	18-12	23-12
HD	12	12	12	12	12	12	12	12	12	12	12
DA	15°	15°	15°	15°	15°	15°	15°	15°	15°	15°	15°
Ext	8	8	8	8	8	8	8	8	8	8	8
Comp	15	15	15	15	15	15	15	15	15	15	15
Kgs	1.94	2.14	2.67	3.14	3.57	4.10	5.56	6.70	8.90	9.96	15.93




HD - Horizontal Displacement



DA - Deflection Angular



Ext - Extension



Comp - Compression

