




## RT Stainless Steel 316 Reducing Tee




### Features

- Made from CF8M (316) Stainless Steel material and conform to ISO 4144 standard.
- Threads are to BSP Parallel (ISO 7/1).
- Material certificates available on request.
- Tested & inspected prior to despatch.
- 12 month warranty from date of installation.
- Manufactured in accordance with ISO9001:2015 quality system.



DN	A	B	C	D	Kgs
3/8" x 1/4"	22.0	20.0	20.3	17.6	0.047
1/2" x 1/4"	24.0	24.0	27.0	17.6	0.085
1/2" x 3/8"	25.0	26.0	27.0	20.3	0.086
3/4" x 1/2"	30.0	29.0	32.0	27.0	0.130
1" x 3/4"	36.0	34.0	40.3	32.0	0.224
1 1/4" x 1"	42.0	40.0	48.3	40.3	0.340
1 1/2" x 1 1/4"	48.0	45.0	55.0	47.8	0.442
2" x 1 1/2"	55.0	52.0	67.3	55.0	0.645



Temperature (°C)	Non-shock maximum working pressure (bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

- NOTE 1 Pressure for intermediate temperatures may be determined by the interpolation method.
- NOTE 2 Temperatures indicated are those of internal fluid.
- NOTE 3 Piping loads, stresses and moments are not taken into account.